## Tree Thinning Saves Lives and Property!

Patrick J. Valerio

For example, the forests surrounding the Weapons Engineering Tritium Facility (WETF) and TA-54 facilities were mitigated in 1999 for wildfire prevention using the above mentioned parameters with the

The Cerro Grande fire approached both facilities, and both facilities received no physical damage as a direct result of tree thinning and surface fuel reduction. The fires remained on the ground, and the Los Alamos Fire Department was able to control them. In addition, the fire intensities experienced at LANL, in general, from the Cerro Grande fire, were significantly lower than those experienced by the Santa Fe





LANL's forest management objective is to have a diverse forest structure (in regard to tree sizes, age classes, and densities) present in a mosaic pattern with a herbaceous and grass understory that is resistant to high-intensity wildfires and can be perpetuated in a healthy condition with selective cutting and





This condition emulates conditions that would exist under a natural fire regime in which higher-frequency, low-intensity surface fires kept the fuel load and tree density low. The treated areas appear more park-like with an increase in the diversity of shrubs, herbs, and grasses in the understory. The desired end-state forest conditions would fall within the following parameters:

This condition emulates conditions that would

- Individual tree crowns would be separated by a distance of about 10 to 25 ft (3 to 7.6 m).
- Tree group crown would be separated by a distance of about 40 ft (12 m) from each other.
- Tree density would be about 50 to 150 trees per ac (20 to 60 trees per ha).
- Canopy cover would be between 40 percent to 60 percent of the project area.
- · Ladder fuels would be removed.
- Ground fuels would not exceed 4 tons per ac (1.5 t/ha).
- The majority of trees to be removed would be 9 in. (22.4 cm) in diameter breast height (dbh) or less
- Some trees 12 to 16 in. (29.5 to 40.6 cm) dbh may be removed to achieve the desired
- may be removed to achieve the desired spacings.

   Fuel breaks would be developed in about a 200-1t (60-m) radius around buildings using a tree spacing of about 20 ft (6 m).

  Diseased, infected, or weakened trees would be preferentially removed during thinning treatments.











Thinning consists of mechanically reducing the density of understory vegetation and trees by selective cutting. Understory thinning removes select woody vegetation, fallen trees and limbs, and low-growing tree limbs that could act as so- called "ladder growing tere timbs that could act as so'cancel adout-fuel" to carry a surface fire upward into the tree crowns. Tree thinning removes select trees to interrupt the continuity of the forest canopy and, consequently, the potential for a crown fire to spread. Trees selected for thinning would be marked at least 6 in. (15 cm) above the ground and on the side away from trails or potential public viewing areas. Remaining tree stumps would be 6 in. (15 cm) or less tall. Large, fire-resistant species of trees, e.g., ponderosa pines, would be retained to increase the fire resistance of the forest.







pre-treatment wildfire rating "moderate" post treatment wildfire rating "very low" pre treatment wildfire rating "moderate" post treatment wildfire rating "low"

following results:





